

Certification Record

CUSTOMER	CLASS	FILE NUMBER
Sato Parts Co., Ltd. 3-3-8, Sotokanda, Chiyoda-ku Tokyo Japan 101-0021	6225-01 FUSEHOLDER ASSEMBLIES-	065927_0_000

Extractor type fuseholders, intended for through-the-panel mounting:

- Cat No F-70, 30A and less, 250V ac and less, for use with 6.35mm by 31.8mm cartridge fuses.
- Cat No F-75, 10A and less, 250V ac and less, for use with 5.2mm by 20mm cartridge fuses.
- Cat No F-85, 10A and less, 250V ac and less, for use with 6.4mm by 30mm or 6.35mm by 31.8mm cartridge fuses.
- Type F-120, 10A and less, 250V ac and less, for use with 6.4 by 30mm or 6.35 by 31.8mm cartridge fuses.
- Type F-130, 10A and less, 250V ac and less, for use with 6.4 by 30mm or 6.35 by 31.8mm cartridge fuses.
- Type F-140, 10A and less, 250V ac and less, for use with 5.2mm by 20mm cartridge fuses.
- Type F-150, 10A and less, 250V ac and less, for use with 6.4mm by 30mm or 6.35mm by 31.8mm cartridge fuses.

- Cat Series F-220 with suffixes, 16A and less, 250V ac and less, for use with 5.2 by 20mm, 6.4 by 30mm and 6.35 by 31.8mm cartridge fuses.
- Cat No F-240, 10A and less, 250V ac and less, for use with 6.4 by 30mm or 6.35 by 31.8mm cartridge fuses.

Extractor type fuseholders, intended for printed circuit board mounting:

- Cat No F-33S, 6A and less, 250V ac and less, for use with 5.2mm by 20mm cartridge fuses.
- Cat No F-33L, 8A and less, 250V ac and less, for use with 6.4mm by 30mm or 6.35mm by 31.8mm cartridge fuses.
- Cat Nos F-100, F-105, 10A and less, 250V ac and less, for use with 5.2mm by 20mm cartridge fuses.
- Cat No F-110, 10A and less, 250V ac and less, for use with 6.4mm by 30mm or 6.35 mm by 31.8 mm cartridge fuses.
- Cat Series F-230 with suffixes, 16A and less, 250V ac and less, for use with 5.2 by 20mm, 6.4 by 30mm and 6.35 by 31.8mm cartridge fuses. Open type fuseholders, single pole:
- Cat No F-60, 5A and less, 125V ac and less for use with 5.2mm by 20mm cartridge fuses.
- Cat No F-61, 10A and less, 250V ac and less for use with 6.4mm by 30mm or 6.35mm by 31.8mm cartridge fuses.
- Cat No F-64, 10A and less, 250V ac and less for use with 5.2mm by 20mm cartridge fuses.
- Cat No F-65, 10A and less, 250V ac and less for use with 6.4mm by 30mm or 6.35mm by 31.8mm cartridge fuses.
- Cat No F-66, 20A and less, 250V ac and less for use with 10.31mm by 38.1mm cartridge fuses.
- Type F-200, 10A and less, 250V ac and less, for use with 6.35 by 31.8mm or 6.4 by 30.0mm cartridge fuses. Open type fuseholders, 1 and 2-pole:
- Type F-180, 10A and less, 250V ac and less, for use with 6.35 by 31.8mm or 6.4 by 30.0mm cartridge fuses. Note: These fuseholders are Certified as components for use only in other Certified equipment where the suitability of the combination is determined by the Canadian Standards Association.
- Fuseholders for cartridge ferrule fuses, suitable for PWB mounting, 1-pole, 2-pole, or 3-pole, model series F-300, rated 250 V, 5A. Note: These fuseholders are supplied only to manufacturers, as components, for the assembly of certified electrical equipment and the suitability of the combination will be determined on the final product.
- Fuseholders, extractor type, intended for panel mounting, Model F-250, rated 250 V ac, 20 A.

Note: These fuseholders are certified as components for use in the assembly of certified electrical equipment and the suitability of the combination will be determined on the final product.

- Fuseholders for cartridge ferrule fuses, dimensions of 6.35 diameter by 31.8 mm long or 6.4 diameter by 30.0 mm long fuses, suitable for PWB mounting, 1-pole or 2-pole, Model Series F-350, rated 250 V, 10 A.

Note: These fuseholders are supplied only to manufacturers, as components, for the assembly of certified electrical equipment and the suitability of the combination will be determined on the final product.