

Zertifikat Certificate

mit überwachter Konformität of surveyed conformity



Zertifikat Nr. Certificate No.
J 50070639

Blatt Page
0001

Ihr Zeichen Client Reference
ML-2200-1

Unser Zeichen Our Reference
ZJL-CDR- 12011111 002

Ausstellungsdatum
14.10.2005

Date of Issue
(day/mo/yr)

Genehmigungsinhaber License Holder
Sato Parts Co., Ltd.
3-3-3 Ebisu
Shibuya-ku, Tokyo 150-0013
Japan

Fertigungsstätte Manufacturing Plant
Niigata Sato Parts Co., Ltd.
2255-2 Torigoe
Nagaoka-shi, Niigata 940-2316
Japan

Prüfzeichen Test Mark

Geprüft nach Tested acc. to

EN 60947-7-1:2002



Zertifiziertes Produkt (Geräteidentifikation)
Certified Product (Product Identification)

Lizenzentgelte - Einheit
License Fee - Unit

PCB Terminal Block

Type Designation : ML-2200-x-yP-z	5
x = S1 or W1S1	1
y = 2 to 20 (even number only) for S1 or 4 to 40 (even number only) for W1S1	1
z = max. 15 digit(s) or blank	1
Dashes are optional	
Number of Poles : 2 to 20 (for x=S1) 4 to 40 (for x=W1S1)	
Rated Voltage : AC/DC 320V, 50/60Hz (see Appendix 1) AC/DC 200V, 50/60Hz (see Appendix 1)	
Rated Current : 3A	
Rated Withstand Impulse Voltage : AC 4000V	
Overvoltage Category : III	
Pollution Degree : 2 or 3 (see Appendix 1)	
IP Degree : IP00	
Upper/Lower Limit Temperature : 105°C/-40°C	
Max. Ambient Temperature at Rated Current : 70°C	
Remark : Replaces J 50070639 page 0001, dated 20.09.2005.	

8

ANLAGE (Appendix) : 1

Dem Zertifikat liegt unsere Prüf- und Zertifizierungsordnung zugrunde.
Das Produkt entspricht den o.g. Anforderungen, die Herstellung wird überwacht.
This certificate is based on our Testing and Certification Regulation. The product
fulfills above-mentioned requirements, the production is subject to surveillance.



Zertifizierungsstelle

TÜV Rheinland Product Safety GmbH, Am Grauen Stein, D-51105 Köln

Dipl.-Ing. M. Geiser

Zertifikat

mit überwachter Konformität of surveyed conformity

Certificate



Zertifikat Nr. *Certificate No.*
J 50070639

Blatt *Page*
0002

Ihr Zeichen *Client Reference*
ML-2200-2

Unser Zeichen *Our Reference*
ZJL-CDR- 12011111 003

Ausstellungsdatum
26.05.2006

Date of Issue
(day/month/year)

Genehmigungsinhaber *License Holder*
Sato Parts Co., Ltd.
3-3-3 Ebisu
Shibuya-ku, Tokyo 150-0013
Japan

Fertigungsstätte *Manufacturing Plant*
Niigata Sato Parts Co., Ltd.
2255-2 Torigoe
Nagaoka-shi, Niigata 940-2316
Japan

Prüfzeichen *Test Mark*

Geprüft nach *Tested acc. to*



EN 60947-7-1:2002

Zertifiziertes Produkt (Geräteidentifikation)
Certified Product (Product Identification)

Lizenzentgelte - Einheit
License Fee - Unit

PCB Terminal Block

Change

Upper Limit Temperature : 105°C

changed to : 80°C

Dem Zertifikat liegt unsere Prüf- und Zertifizierungsordnung zugrunde.
Das Produkt entspricht den o.g. Anforderungen, die Herstellung wird überwacht.
This certificate is based on our Testing and Certification Regulation. The product
fulfills above-mentioned requirements, the production is subject to surveillance.



Zertifizierungsstelle

TÜV Rheinland Product Safety GmbH, Am Grauen Stein, D-51105 Köln

Dipl.-Ing. M. Geiser

Zertifikat

mit überwachter Konformität of surveyed conformity

Certificate



Zertifikat Nr. Certificate No.
J 50070639

Blatt Page
0003

Ihr Zeichen Client Reference
NL-2200-3

Unser Zeichen Our Reference
ZJL-CDR- 12011111 004

Ausstellungsdatum
19.09.2006

Date of Issue
(day/mo/yr)

Genehmigungsinhaber License Holder
Sato Parts Co., Ltd.
3-3-3 Ebisu
Shibuya-ku, Tokyo 150-0013
Japan

Fertigungsstätte Manufacturing Plant
Niigata Sato Parts Co., Ltd.
2255-2 Torigoe
Nagaoka-shi, Niigata 940-2316
Japan

Prüfzeichen Test Mark

Geprüft nach Tested acc. to



EN 60947-7-1:2002

Zertifiziertes Produkt (Geräteidentifikation)
Certified Product (Product Identification)

Lizenzentgelte - Einheit
License Fee - Unit

PCB Terminal Block

Changes

for Type Designation ML-2200-x-yP-z :

Suffix : y = 2 to 20 (even number only) for S1 or
4 to 40 (even number only) for W1S1

changed to : y = 2 to 50 for S1 or
4 to 100 (even number only) for W1S1

Number of Poles : 2 to 20 (for x=S1) 4 to 40 (for x=W1S1)

changed to : 2 to 50 (for x=S1) 4 to 100 (for x=W1S1)

ANLAGE (Appendix) : 1.1

Dem Zertifikat liegt unsere Prüf- und Zertifizierungsordnung zugrunde.
Das Produkt entspricht den o.g. Anforderungen, die Herstellung wird überwacht.
This certificate is based on our Testing and Certification Regulation. The product
fulfills above-mentioned-requirements, the production is subject to surveillance.

TÜV Rheinland Product Safety GmbH, Am Grauen Stein, D-51105 Köln



Zertifizierungsstelle

Dipl.-Ing. M. Geiser

Zertifikat **Certificate**
mit überwachter Konformität of surveyed conformity



Zertifikat Nr. *Certificate No.*
J 50070639

Blatt *Page*
0004

Ihr Zeichen *Client Reference*
--

Unser Zeichen *Our Reference*
ZJL-MIU- 12011111 006

Ausstellungsdatum
01.06.2012

Date of Issue
(day/mo/yr)

Genehmigungsinhaber *License Holder*
Sato Parts Co., Ltd.
3-3-3 Ebisu
Shibuya-ku, Tokyo
150-0013 JAPAN

Fertigungsstätte *Manufacturing Plant*
Niigata Sato Parts Co., Ltd.
2255-2 Torigoe
Nagaoka-shi, Niigata
940-2316 JAPAN

Prüfzeichen *Test Mark*

Geprüft nach *Tested acc. to*



EN 60947-7-1:2009

Zertifiziertes Produkt (Geräteidentifikation)
Certified Product (Product Identification)

Lizenzentgelte - Einheit
License Fee - Unit

PCB Terminal Block, as page 0001

Change

Test Requirement : EN 60947-7-1:2002

changed to : (see above)

Dem Zertifikat liegt unsere Prüf- und Zertifizierungsordnung zugrunde.
Das Produkt entspricht den o.g. Anforderungen, die Herstellung wird überwacht.
This certificate is based on our Testing and Certification Regulation. The product
fulfills above mentioned requirements, the production is subject to surveillance.



Zertifizierungsstelle

TÜV Rheinland LGA Products GmbH, Tillystraße 2, 90431 Nürnberg
Tel.: +49 221 806-1371 e-mail: cert-validity@de.tuv.com
Fax: +49 221 806-3935 <http://www.tuv.com/safety>

Dipl.-Ing. (FH) M. Geiser

Zertifikat *Certificate*
mit überwachter Konformität *of surveyed conformity*



Zertifikat Nr. *Certificate No.*
J 50070639

Blatt *Page*
0005

Ihr Zeichen *Client Reference*
FACH-NGT

Unser Zeichen *Our Reference*
ZJL-MAA- 12011111 007

Ausstellungsdatum
30.04.2015

Date of Issue
(day/month/year)

Genehmigungsinhaber *License Holder*
Sato Parts Co., Ltd.
3-3-3 Ebisu
Shibuya-ku, Tokyo
150-0013 JAPAN

Fertigungsstätte *Manufacturing Plant*
Sato Parts Co., Ltd. Niigata Factory
2255-2 Torigoe
Nagaoka-shi, Niigata
940-2316 JAPAN

Prüfzeichen *Test Mark*

Geprüft nach *Tested acc. to*



EN 60947-7-1:2009

Zertifiziertes Produkt *(Geräteidentifikation)*
Certified Product (Product Identification)

Lizenzentgelte - Einheit
License Fee - Unit

PCB Terminal Block, as page 0001

Change

Name of Factory: Niigata Sato Parts Co., Ltd.

changed to: (see above)

Dem Zertifikat liegt unsere Prüf- und Zertifizierungsordnung zugrunde.
Das Produkt entspricht den o.g. Anforderungen, die Herstellung wird überwacht.
This certificate is based on our Testing and Certification Regulation. The product
fulfills above mentioned requirements, the production is subject to surveillance.



Zertifizierungsstelle

TÜV Rheinland LGA Products GmbH, Tillystraße 2, 90431 Nürnberg
Tel.: +49 221 806-1371 e-mail: cert-validity@de.tuv.com
Fax: +49 221 806-3935 http://www.tuv.com/safety

Vilmos Sztaroveczki

Zertifikat *Certificate*
mit überwachter Konformität *of surveyed conformity*



Zertifikat Nr. *Certificate No.*
J 50070639

Blatt *Page*
0006

Ihr Zeichen *Client Reference*
TUV-ADD-CH

Unser Zeichen *Our Reference*
ZJL-MAA- 12011111 007

Ausstellungsdatum *Date of Issue*
27.09.2016
(day/mo/yr)

Genehmigungsinhaber *License Holder*
Sato Parts Co., Ltd.
3F Sanyu Bldg. 3-42-1, Hongo
Bunkyo-ku, Tokyo
113-0033 Japan

Fertigungsstätte *Manufacturing Plant*
Sato Parts Co., Ltd. Niigata Factory
2255-2 Torigoe
Nagaoka-shi, Niigata
940-2316 Japan

Prüfzeichen *Test Mark*

Geprüft nach *Tested acc. to*



EN 60947-7-1:2009

Zertifiziertes Produkt *(Geräteidentifikation)*
Certified Product (Product Identification)

Lizenzentgelte - Einheit
License Fee - Unit

PCB Terminal Block, as page 0001

Change

Address of
License Holder: 3-3-3 Ebisu, Shibuya-ku, Tokyo
150-0013 JAPAN

changed to: (see above)



Zertifizierungsstelle

Dem Zertifikat liegt unsere Prüf- und Zertifizierungsordnung zugrunde.
Das Produkt entspricht den o.g. Anforderungen, die Herstellung wird überwacht.
This certificate is based on our Testing and Certification Regulation. The product
fulfills above mentioned requirements, the production is subject to surveillance.

TÜV Rheinland LGA Products GmbH, Tillystraße 2, 90431 Nürnberg
Tel.: +49 221 806-1371 e-mail: cert-validity@de.tuv.com
Fax: +49 221 806-3935 <http://www.tuv.com/safety>

Vilmos Sztaroveczki

Zertifikat *Certificate*
mit überwachter Konformität *of surveyed conformity*



Zertifikat Nr. *Certificate No.*
J 50070639

Blatt *Page*
0007

Ihr Zeichen *Client Reference*
ADD-CH

Unser Zeichen *Our Reference*
ZJL-MAA- 12011111 007

Ausstellungsdatum
27.02.2020

Date of Issue
(day/mo/yr)

Genehmigungsinhaber *License Holder*
Sato Parts Co., Ltd.
3-3-8, Sotokanda,
Chiyoda-ku, Tokyo
101-0021 Japan

Fertigungsstätte *Manufacturing Plant*
Sato Parts Co., Ltd. Niigata Factory
2255-2 Torigoe
Nagaoka-shi, Niigata
940-2316 Japan

Prüfzeichen *Test Mark*

Geprüft nach *Tested acc. to*



EN 60947-7-1:2009

Zertifiziertes Produkt *(Geräteidentifikation)*
Certified Product (Product Identification)

Lizenzentgelte - Einheit
License Fee - Unit

PCB Terminal Block, as page 0001

Change

Address of
License Holder: 3F Sanyu Bldg. 3-42-1, Hongo
Bunkyo-ku, Tokyo
113-0033 Japan

changed to: (see above)



Dem Zertifikat liegt unsere Prüf- und Zertifizierungsordnung zugrunde.
Das Produkt entspricht den o.g. Anforderungen, die Herstellung wird überwacht.
This certificate is based on our Testing and Certification Regulation. The product
fulfills above mentioned requirements, the production is subject to surveillance.

Zertifizierungsstelle

TÜV Rheinland LGA Products GmbH, Tillystraße 2, 90431 Nürnberg
Tel.: +49 221 806-1371 e-mail: cert-validity@de.tuv.com
Fax: +49 221 806-3935 http://www.tuv.com/safety

Dipl.-Ing. (FH) F. Becker

Constructional Data Form

Page 1/3

Licenseholder : **Sato Parts Co., Ltd.**
 3-3-3 Ebisu, Shibuya-ku, Tokyo 150-0013 Japan
 Factory : **Niigata Sato Parts Co., Ltd**
 (full address) 2255-2 -Torigoe, Nagaoka-shi, Niigata 940-2316 Japan.
 Type or Model Number : **ML-2200 series**
 Kind of device: **Terminal Block**

Specifications	
Type designation	ML-2200 series
Contact material	Copper Alloy (Plated)
Number of poles	S1: 2 to 50 W1S1: 4 to 100
Rated voltage	AC/DC 320V (Pollution degree 2 without spacer) AC/DC 320V (Pollution degree 3 with spacer) AC/DC 200V (Pollution degree 3 without spacer)
Rated current	3A
Rated frequency	AC 50/60
Rated withstand impulse voltage	AC 4000V
Breaking Capacity	AC 2000V / 1minute
Mechanical endurance	100 times
Number of bendings	N/A
Overvoltage category	III
Pollution degree	2 or 3
Creepage / Clearance distance (contact-contact)	$\geq 3.3/\geq 3.3\text{mm}(\text{without spacer}) \geq 5.8\text{mm}/\geq 5.8\text{mm}(\text{with spacer})$
Upper limit temperature	80°C
Lower limit temperature	-40°C
Max. ambient temp. at rated current	70°C
IP code	00
Classification	☐ CBC ☒ NCB

Köln, den 25.08.2006

TÜV Rheinland
 Product Safety GmbH

Ebisu

(Place)

2006-08-22

(Date)

SATO PARTS Co., Ltd

M.Kosho

(Stamp and Signature of Applicant)

Constructional Data Form

Page 2/3

Specifications (terminals)	
Type of terminals	☐ WRAPPED CONNECTION ☐ CRIMPED CONNECTION ☐ CLIP CONNECTION ☐ PRESS-IN CONNECTIONS ☐ INSULATION DISPLACEMENT CONNECTION ☒ SCREWLESS TERMINALS ☐ SCREW TERMINALS ☐ FLAT, QUICK CONNECT TERMINATIONS ☒ SOLDER TERMINALS ☐ other:
Terminal designation	N/A
Spec. Tightening torque	N/A
Rated cross section of conductor	For flexible conductor: 0.3mm ² ~0.75mm ² (AWG22~20) For rigid conductor: Ø0.4mm~Ø1.2mm (AWG26~18)
Kind of conductor	Flexible / rigid
Required preparation of the conductor	N/A
Max. Stripping length	8.5mm
Max. Number of conductors per Terminal	1

Materials	
Parts' Name	Material
Housing A	Polyamide, Type 66 Nylon R/C plastic (QMFZ2) , File No. : E48133 UBE INDUSTRIES LTD., Type 2015SV, any color, UL94V-0 RTI : 105°C CTI : 0 (PLC)
Housing B	
End plate (S)	
End plate (W)	
Spacer	
Release button	PPEP : Polyphenylene ether(Polyphenylene oxide, PPHOX) R/C plastic(QMFZ2), File No. : E41179, any color MITSUBISHI ENGINEERING-PLASTICS CORP., Type AN60, Flame class(94V-0), CTI : 3(PLC) Polycarbonate(lupilon) : R/C plastic(QMFZ2), File No. : E41179, any color MITSUBISHI ENGINEERING-PLASTICS CORP., Type FPR3500+, Flame class(94V-0), CTI : 2(PLC) Polyamide (66 Nylon) : R/C plastic(QMFZ2), File No. : E48133, any color, UBE INDUSTRIES LTD, Type : 2015SV, Flame class(94V-0), CTI : 0 (PLC)
Spring	One provided per pole. Stainless steel, 5.86 by 4.85 by 3.4mm overall, 0.25mm thick. Secured to wire terminal by one notch.
Wire terminal	Copper alloy (Plated)
Wire terminal (T)	Copper alloy (Plated)

Köln, den 25 AUG, 2006

TÜV Rheinland
 Product Safety GmbH

Ebisu

(Place)

2006-08-22

(Date)

SATO PARTS Co., Ltd

M.Kosho

(Stamp and Signature of Applicant)

Constructional Data Form

Page 3/3

TYPE NOMENCLATURE:

Example : ML-2200 — x — yP — z
 A

A — Basic construction (Model No.)

x — Terminal formation

S1 : One row type
W1S1 : Two rows type

y — Number of poles

2 to 50 for S1
4 to 100 (even number only) for W1S1

z — Suffix : Blank or maximum 15 digit(s) numbers and/or letters such as drawing numbers.
Example; Specified drawing number that denote specified colors of the body.

Note : Dashes are optional.

Köln, den 25. Aug. 2006


TÜV Rheinland
Product Safety GmbH

Ebisu

(Place)

2006-08-22

(Date)

SATO PARTS Co., Ltd

M. Kosho

(Stamp and Signature of Applicant)

NOTICE OF ALTERATIONS/MODIFICATION (変更通知)

Applicant (申請会社名) : Sato Parts Co., Ltd. (サトーパーツ株式会社)

Signature: D. Sato

(サイン)

Ref. No.: _____

Date: 2012/11/9

Page: 1/1

Product (製品名) : TERMINAL BLOCK


Type designation (型式) : ML-2200 series

Report No.: _____

License No.: J 50070639

Methods (Design / Component) Presently Employed (変更前 : 現行)		Alteration/Modification to be Introduced (変更後)	
Part's Name	Material	Part's Name	Material
Housing A	Polyamide, Type 66 Nylon	Housing A	Polyamide, Type 66 Nylon
Housing B		Housing B	
End plate (S)		End plate (S)	
End plate (W)		End plate (W)	
Spacer		Spacer	
	R/C plastic (QMFZ2) , File No.:E48133 UBE INDUSTRES LTD., Type 2015SV,any color, UL94V-0 RTI: 105°C CTI:0(PLC)		R/C plastic (QMFZ2) , File No.:E48133 UBE INDUSTRES LTD., Type 2015SV,any color, UL94V-0 RTI: 105°C CTI:0(PLC)
	R/C plastic (QMFZ2) , File No.:E48133 UBE INDUSTRES LTD., Type 2015SE,any color, UL94V-0 RTI: 105°C CTI:0(PLC)		R/C plastic (QMFZ2) , File No.:E48133 UBE INDUSTRES LTD., Type 2015SE,any color, UL94V-0 RTI: 105°C CTI:0(PLC)
	R/C plastic (QMFZ2) , File No.:E48285 ASAHI KASEI CHEMICALS CORP., Type FR370, any color, UL94V-0 RTI: 105°C CTI:0(PLC)		R/C plastic (QMFZ2) , File No.:E48285 ASAHI KASEI CHEMICALS CORP., Type FR370, any color, UL94V-0 RTI: 105°C CTI:0(PLC)
			Alternate: R/C plastic (QMFZ2) , File No.:E245249 LANXESS AG, Type A30SFN31, any color, UL94V-0 RTI: 125°C CTI:0(PLC)


 TUV Rheinland Japan
 Genehmigt/Approved
 2012-11-14


 Ref. No.:
 12011111 007

● 記入の仕方: 変更前(現行)と変更後の対比、違いが明確に理解できる書き方(英語)をお願いします。特に1次側の変更か2次側の変更かを明記下さい。

NOTICE OF ALTERATIONS/MODIFICATION

(変更通知)

Applicant (申請会社名) : Sato Parts Co., Ltd. (サトーパーツ株式会社)

Date: 2009/8/17

Signature: Y. SAKURAGI
(サイン)


Ref. No.: ZJL-CDR-12011111 004

Page: 2/2

Product (製品名) : TERMINAL BLOCK Type designation (型式) : ML-2200 series

Report No.: 12011111 005 License No.: J 50070639

Methods (Design / Component) Presently Employed (変更前 : 現行)		Alteration/Modification to be Introduced (変更後)	
Part's Name	Material	Part's Name	Material
Release button	PPEP: Ployphenylene ether(Polyphenylene oxide, PPHOX) R/C plastic(QMFZ2), File No.: E41179, any color MITSUBISHI ENGINEERING-PLASTICS CORP., Type AN60, Flame class(94V-0), CTI:0(PLC) Polycarbonate(lupilon): R/C plastic(QMFZ2), File No.: E41179, any color MITSUBISHI ENGINEERING-PLASTICS CORP., Type FPR3500+, Flame class(94V-0), CTI:2(PLC) Polyamide(66 Nylon): R/C plastic(QMFZ2), File No.: E48133, any color, UBE INDUSTRIES LTD, Type: 2015SV, Flame class(94V-0), CTI: 0(PLC)	Release button	PPEP: Ployphenylene ether(Polyphenylene oxide, PPHOX) R/C plastic(QMFZ2), File No.: E41179, any color MITSUBISHI ENGINEERING-PLASTICS CORP., Type AN60, Flame class(94V-0), CTI:0(PLC) Alternate: R/C plastic(QMFZ2), File No.: E41179, any color MITSUBISHI ENGINEERING-PLASTICS CORP., Type LN60, Flame class(94V-0), CTI:0(PLC) Polycarbonate(lupilon): R/C plastic(QMFZ2), File No.: E41179, any color MITSUBISHI ENGINEERING-PLASTICS CORP., Type FPR3500+, Flame class(94V-0), CTI:2(PLC) Polyamide(66 Nylon): R/C plastic(QMFZ2), File No.: E48133, any color, UBE INDUSTRIES LTD, Type: 2015SV, Flame class(94V-0), CTI: 0(PLC)
Spring	One provided per pole. Stainless steel, 5.86 by 4.85 by 3.4mm overall, 0.25mm thick. Secured to wire terminal by one notch.	Spring	One provided per pole. Stainless steel, 5.86 by 4.85 by 3.4mm overall, 0.25mm thick. Secured to wire terminal by one notch.
Wire terminal	Copper alloy (Plated)	Wire terminal	Copper alloy (Plated)
Wire terminal (T)	Copper alloy (Plated)	Wire terminal (T)	Copper alloy (Plated)



● 記入の仕方 : 変更前 (現行) と変更後の対比、違いが明確に理解できる書き方 (英語) でお願いします。特に 1 次側の変更か 2 次側の変更かを明記下さい。

NOTICE OF ALTERATIONS/MODIFICATION

(変更通知)

Applicant (申請会社名): **SATO PARTS CO., LTD.**

Date: 2006-04-12

Signature: M. Sato
(サイン)

Ref. No.: ML-2200-2

Page: (1/1)

Product (製品名): TERMINAL BLOCKS

Type designation (型式): ML-2200

Report No.: 1201111

License No.: J50070639

Methods (Design / Component) Presently Employed (変更前 : 現行)	Alteration/Modification to be Introduced (変更後)																								
 <table border="1" style="margin: 20px auto; width: 80%; border-collapse: collapse;"> <thead> <tr> <th style="width: 10%;"></th> <th style="width: 90%;">Material For release button</th> </tr> </thead> <tbody> <tr> <td style="text-align: center;">Material</td> <td>PPE, Polyphenylene Oxide (PPHOX)</td> </tr> <tr> <td style="text-align: center;">Maker</td> <td>Mitsubishi Engineering-plastics corp</td> </tr> <tr> <td style="text-align: center;">Type</td> <td>Type : AN60 , any color, UL94V-0, File No. : E41179 CTI : 3(PLC)</td> </tr> </tbody> </table> 		Material For release button	Material	PPE, Polyphenylene Oxide (PPHOX)	Maker	Mitsubishi Engineering-plastics corp	Type	Type : AN60 , any color, UL94V-0, File No. : E41179 CTI : 3(PLC)	<table border="1" style="margin: 20px auto; width: 90%; border-collapse: collapse;"> <thead> <tr> <th style="width: 10%;"></th> <th colspan="3" style="width: 90%;">Material for release button</th> </tr> </thead> <tbody> <tr> <td style="text-align: center;">Material</td> <td>PPE, Polyphenylene Oxide (PPHOX)</td> <td>Polyamide, 66 Nylon</td> <td>Polycarbonate (Iupilon)</td> </tr> <tr> <td style="text-align: center;">Maker</td> <td>Mitsubishi Engineering-plastics corp</td> <td>UBE INDUSTRIES LTD</td> <td>Mitsubishi Engineering-plastics corp</td> </tr> <tr> <td style="text-align: center;">Type</td> <td>Type : AN60 , any color, UL94V-0, File No. : E41179 RTI : 105°C, CTI : 3(PLC)</td> <td>Type : 2015SV, any color, UL94V-0, File No. : E48133 RTI : 105°C, CTI : 0 (PLC)</td> <td>Type : FPR3500+, any color, UL94V-0, File No. : E41179 RTI : 80°C, CTI : 2(PLC)</td> </tr> </tbody> </table> Registered material for release button change to three types from one type. Upper limit temperature change to 80°C from 105°C. 		Material for release button			Material	PPE, Polyphenylene Oxide (PPHOX)	Polyamide, 66 Nylon	Polycarbonate (Iupilon)	Maker	Mitsubishi Engineering-plastics corp	UBE INDUSTRIES LTD	Mitsubishi Engineering-plastics corp	Type	Type : AN60 , any color, UL94V-0, File No. : E41179 RTI : 105°C, CTI : 3(PLC)	Type : 2015SV, any color, UL94V-0, File No. : E48133 RTI : 105°C, CTI : 0 (PLC)	Type : FPR3500+, any color, UL94V-0, File No. : E41179 RTI : 80°C, CTI : 2(PLC)
	Material For release button																								
Material	PPE, Polyphenylene Oxide (PPHOX)																								
Maker	Mitsubishi Engineering-plastics corp																								
Type	Type : AN60 , any color, UL94V-0, File No. : E41179 CTI : 3(PLC)																								
	Material for release button																								
Material	PPE, Polyphenylene Oxide (PPHOX)	Polyamide, 66 Nylon	Polycarbonate (Iupilon)																						
Maker	Mitsubishi Engineering-plastics corp	UBE INDUSTRIES LTD	Mitsubishi Engineering-plastics corp																						
Type	Type : AN60 , any color, UL94V-0, File No. : E41179 RTI : 105°C, CTI : 3(PLC)	Type : 2015SV, any color, UL94V-0, File No. : E48133 RTI : 105°C, CTI : 0 (PLC)	Type : FPR3500+, any color, UL94V-0, File No. : E41179 RTI : 80°C, CTI : 2(PLC)																						

- 記入の仕方: 変更前(現行)と変更後の対比、違いが明確に理解できる書き方(英語)をお願いします。
特に1次側の変更か2次側の変更かを明記下さい。

Rep. No.: 1201111 003

NOTICE OF ALTERATIONS/MODIFICATION

(変更通知)

Applicant (申請会社名): Sato Parts Co., Ltd.

Date: 2023-12-5

Signature (サイン): Yutaka Kodama

Ref. No.:

Page: 1 of 2


Product (製品名): Terminal Block

Type designation (型式): ML-2200-x-yP-z

Report No.: 12011111 008

License No.: J 50070639

Methods (Design / Component) Presently Employed (変更前 : 現行)		Alteration/Modification to be Introduced (変更後)	
Insulating Materials		Insulating Materials	
Parts Name	Material	Parts Name	Material
Housing A Housing B End Plate (S) End Plate (W) Spacer	Polyamide, Type 66 Nylon	Housing A Housing B End Plate (S) End Plate (W) Spacer	Polyamide, Type 66 Nylon
	R/C plastic (QMFZ2), File No. E48133 UBE INDUSTRIES LTD., Type 2015SV, any color, UL94V-0 RTI: 105°C CTI: 0 (PLC)		R/C plastic (QMFZ2), File No. E48285 ASAHI KASEI CORP., Type FR370, any color, UL94V-0 RTI: 105°C CTI: 0 (PLC)
	R/C plastic (QMFZ2), File No. E48133 UBE INDUSTRIES LTD., Type 2015SE, any color, UL94V-0 RTI: 105°C CTI: 0 (PLC)		R/C plastic (QMFZ2), File No. E245249 LANXESS AG, Type A30SFN31, any color, UL94V-0 RTI: 125°C CTI: 0 (PLC)
	R/C plastic (QMFZ2), File No. E48285 ASAHI KASEI CHEMICALS CORP., Type FR370, any color, UL94V-0 RTI: 105°C CTI: 0 (PLC)		
Alternate: R/C plastic (QMFZ2), File No. E245249 LANXESS AG, Type A30SFN31, any color, UL94V-0 RTI: 125°C CTI: 0 (PLC)			



● 記入の仕方: 変更前 (現行) と変更後の対比、違いが明確に理解できる書き方 (英語) でお願いします。
特に 1 次側の変更か 2 次側の変更かを明記下さい。

NOTICE OF ALTERATIONS/MODIFICATION

(変更通知)

Applicant (申請会社名):	Sato Parts Co., Ltd.	Date:	2023-12-5
Signature (サイン):	Yutaka Kodama	Ref. No.:	Page: 2 of 2
Product (製品名):	Terminal Block	Type designation (型式):	ML-2200-x-yP-z
Report No.:		License No.:	J 50070639

Methods (Design / Component) Presently Employed (変更前 : 現行)	Alteration/Modification to be Introduced (変更後)																							
<table><tr><th colspan="2">Insulating Materials</th></tr><tr><th>Part's Name</th><th>Material</th></tr><tr><td rowspan="5">Release button</td><td>PPEP: Polyphenylene ether (Polyphenylene oxide, PPHOX)</td></tr><tr><td>R/C plastic (QMFZ2), File No. E41179, any color MITSUBISHI ENGINEERING-PLASTICS CORP., Type AN60, Flame class (94V-0), CTI: 0 (PLC)</td></tr><tr><td>Alternate: R/C plastic (QMFZ2), File No. E41179, any color MITSUBISHI ENGINEERING-PLASTICS CORP., Type LN60, Flame class (94V-0), CTI: 0 (PLC)</td></tr><tr><td>Polycarbonate (Iupilon)</td></tr><tr><td>R/C plastic (QMFZ2), File No. E41179, any color MITSUBISHI ENGINEERING-PLASTICS CORP., Type FPR3500+, Flame class (94V-0), CTI: 2 (PLC)</td></tr><tr><td rowspan="2"></td><td>Polyamide (66 Nylon)</td></tr><tr><td>R/C plastic (QMFZ2), File No. E48133, any color UBE INDUSTRIES LTD., Type 2015SV, Flame class (94V-0), CTI: 0 (PLC)</td></tr></table>	Insulating Materials		Part's Name	Material	Release button	PPEP: Polyphenylene ether (Polyphenylene oxide, PPHOX)	R/C plastic (QMFZ2), File No. E41179, any color MITSUBISHI ENGINEERING-PLASTICS CORP., Type AN60, Flame class (94V-0), CTI: 0 (PLC)	Alternate: R/C plastic (QMFZ2), File No. E41179, any color MITSUBISHI ENGINEERING-PLASTICS CORP., Type LN60, Flame class (94V-0), CTI: 0 (PLC)	Polycarbonate (Iupilon)	R/C plastic (QMFZ2), File No. E41179, any color MITSUBISHI ENGINEERING-PLASTICS CORP., Type FPR3500+, Flame class (94V-0), CTI: 2 (PLC)		Polyamide (66 Nylon)	R/C plastic (QMFZ2), File No. E48133, any color UBE INDUSTRIES LTD., Type 2015SV, Flame class (94V-0), CTI: 0 (PLC)	<table><tr><th colspan="2">Insulating Materials</th></tr><tr><th>Part's Name</th><th>Material</th></tr><tr><td rowspan="3">Release button</td><td>Polyphenylene Ether / Polystyrene (PPE / PS)</td></tr><tr><td>R/C plastic (QMFZ2), File No. E167806, any color GLOBAL POLYACETAL CO., LTD., Type LN60, Flame class (94V-0), CTI: 0 (PLC)</td></tr><tr><td>Polycarbonate</td></tr><tr><td></td><td>R/C plastic (QMFZ2), File No. E41179, any color MITSUBISHI ENGINEERING-PLASTICS CORP., Type FPR3500+, Flame class (94V-0), CTI: 2 (PLC)</td></tr></table>	Insulating Materials		Part's Name	Material	Release button	Polyphenylene Ether / Polystyrene (PPE / PS)	R/C plastic (QMFZ2), File No. E167806, any color GLOBAL POLYACETAL CO., LTD., Type LN60, Flame class (94V-0), CTI: 0 (PLC)	Polycarbonate		R/C plastic (QMFZ2), File No. E41179, any color MITSUBISHI ENGINEERING-PLASTICS CORP., Type FPR3500+, Flame class (94V-0), CTI: 2 (PLC)
Insulating Materials																								
Part's Name	Material																							
Release button	PPEP: Polyphenylene ether (Polyphenylene oxide, PPHOX)																							
	R/C plastic (QMFZ2), File No. E41179, any color MITSUBISHI ENGINEERING-PLASTICS CORP., Type AN60, Flame class (94V-0), CTI: 0 (PLC)																							
	Alternate: R/C plastic (QMFZ2), File No. E41179, any color MITSUBISHI ENGINEERING-PLASTICS CORP., Type LN60, Flame class (94V-0), CTI: 0 (PLC)																							
	Polycarbonate (Iupilon)																							
	R/C plastic (QMFZ2), File No. E41179, any color MITSUBISHI ENGINEERING-PLASTICS CORP., Type FPR3500+, Flame class (94V-0), CTI: 2 (PLC)																							
	Polyamide (66 Nylon)																							
	R/C plastic (QMFZ2), File No. E48133, any color UBE INDUSTRIES LTD., Type 2015SV, Flame class (94V-0), CTI: 0 (PLC)																							
Insulating Materials																								
Part's Name	Material																							
Release button	Polyphenylene Ether / Polystyrene (PPE / PS)																							
	R/C plastic (QMFZ2), File No. E167806, any color GLOBAL POLYACETAL CO., LTD., Type LN60, Flame class (94V-0), CTI: 0 (PLC)																							
	Polycarbonate																							
	R/C plastic (QMFZ2), File No. E41179, any color MITSUBISHI ENGINEERING-PLASTICS CORP., Type FPR3500+, Flame class (94V-0), CTI: 2 (PLC)																							

● 記入の仕方 : 変更前 (現行) と変更後の対比、違いが明確に理解できる書き方 (英語) でお願いします。
特に 1 次側の変更か 2 次側の変更かを明記下さい。