

IZLT2.E101405 - Fuseholders, Cartridge Fuse - Component

Note: We are enhancing our systems and you may notice duplicate entries/missing/outdated data. During this interim period, please contact our Customer Service at <https://www.ul.com/about/locations>.

Fuseholders, Cartridge Fuse - Component

SATO PARTS CO LTD

3-3-8 Sotokanda
Chiyoda-Ku, TOKYO 101-0021 Japan

E101405

Marking: Company name or tradename "SATO PARTS", and model designation.

Note: For additional marking information, refer to the [Guide Information Page](#).

(s): F-105, F-100, F-110, F-115, F-120-A, F-120-B, F-130, F-200N, F-200-N, F-240N, F-240-N, F-300-1P, F-300-2P, F-300-3P, F-33L, F-33S, F-400-01A1, F-400-01A2, F-400-01B1, F-400-01B2, F-4000-A, F-4000-B, F-450, F-500-01A1, F-500-01A2, F-500-01B1, F-500-01B2, F-600, F-60-A, F-60-B, F-60-C, F-610, F-61-A, F-61-B, F-61-C, F-61-D, F-64-AB, F-64-AD, F-64-BB, F-64-BD, F-65-AB, F-65-AD, F-65-BB, F-65-BD, F-66-AD, F-66-AE, F-66-BD, F-66-BE, F-70, F-75, F-750 may be followed by -2P to -30P, F-85

(s): F-700 may be followed by -A or -B, may be followed by L, may be followed by -2P to 30P

(s): F-710 may be followed by -A or -B, may be followed by -2P to -30P

(s): F-720 may be followed by -L, may be followed by -2P to -30P

Last Updated on 2021-03-25

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2021 UL LLC"

IZLT2.GuidelInfo - Fuseholders, Cartridge Fuse - Component

Note: We are enhancing our systems and you may notice duplicate entries/missing/outdated data. During this interim period, please contact our Customer Service at <https://www.ul.com/about/locations>.

[Fuseholders - Component] Fuseholders, Cartridge Fuse - Component

See General Information for Fuseholders - Component

The devices covered under this category are incomplete in certain constructional features or restricted in performance capabilities and are intended for use as components of complete equipment submitted for investigation rather than for direct separate installation in the field. THE FINAL ACCEPTANCE OF THE COMPONENT IS DEPENDENT UPON ITS INSTALLATION AND USE IN COMPLETE EQUIPMENT SUBMITTED TO UL.

USE

This category covers fuseholders intended for use with Class CC, CF, G, H, J, K, R, T, special-purpose and supplementary cartridge fuses, and intended for installation in end-use equipment or products.

CONDITIONS OF ACCEPTABILITY

Consideration is to be given to the Conditions of Acceptability specified in the individual Recognitions when these components are employed in the end-use equipment.

RELATED PRODUCTS

Fuseholders intended to accept supplementary fuses (miscellaneous, miniature and micro) may additionally be covered under Terminal Blocks ([XCFR2](#)).

REQUIREMENTS

The basic standard used to investigate products in this category is [UL 4248-1](#), "Fuseholders - Part 1: General Requirements," in addition to one of the following as applicable:

[UL 4248-4](#), "Fuseholders - Part 4: Class CC"

[UL 4248-5](#), "Fuseholders - Part 5: Class G"

[UL 4248-6](#), "Fuseholders - Part 6: Class H"

[UL 4248-8](#), "Fuseholders - Part 8: Class J"

[UL 4248-9](#), "Fuseholders - Part 9: Class K"

[UL 4248-12](#), "Fuseholders - Part 12: Class R"

[UL 4248-15](#), "Fuseholders - Part 15: Class T"

[UL 4248-17](#), "Outline of Investigation for Fuseholders - Part 17: Class CF Fuses"

UL, in performing its functions in accordance with its objectives, does not assume or undertake to discharge any responsibility of the manufacturer or any other party. UL shall not incur any obligation or liability for any loss, expense or damages, including incidental or consequential damages, arising out of or in connection with the use, interpretation of, or reliance upon this Guide Information.

Last Updated on 2019-09-13

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2021 UL LLC"

IZLT8.E101405 - Fuseholders, Cartridge Fuse Certified for Canada - Component

Note: We are enhancing our systems and you may notice duplicate entries/missing/outdated data. During this interim period, please contact our Customer Service at <https://www.ul.com/about/locations>.

Fuseholders, Cartridge Fuse Certified for Canada - Component

SATO PARTS CO LTD

3-3-8 Sotokanda
Chiyoda-Ku, TOKYO 101-0021 Japan

E101405

Marking: Company name or tradename "SATO PARTS", model designation, and the Recognized Component Mark for Canada 

Note: For additional marking information, refer to the [Guide Information Page](#).

(s): F-115, F-200N, F-200-N, F-240N, F-240-N, F-400-01A1, F-400-01A2, F-400-01B1, F-400-01B2, F-4000-A, F-4000-B, F-450, F-500-01A1, F-500-01A2, F-500-01B1, F-500-01B2, F-600, F-610, F-750 may be followed by -2P to -30P

(s): F-700 may be followed by -A or -B, may be followed by L, may be followed by -2P to 30P

(s): F-710 may be followed by -A or -B, may be followed by -2P to -30P

(s): F-720 may be followed by -L, may be followed by -2P to -30P

Last Updated on 2021-03-25

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2021 UL LLC"

IZLT8.GuidelInfo - Fuseholders, Cartridge Fuse Certified for Canada - Component

Note: We are enhancing our systems and you may notice duplicate entries/missing/outdated data. During this interim period, please contact our Customer Service at <https://www.ul.com/about/locations>.

[Fuseholders Certified for Canada - Component] Fuseholders, Cartridge Fuse Certified for Canada - Component

[See General Information for Fuseholders Certified for Canada - Component](#)

The devices covered under this category are incomplete in certain constructional features or restricted in performance capabilities and are intended for use as components of complete equipment submitted for investigation rather than for direct separate installation in the field. THE FINAL ACCEPTANCE OF THE COMPONENT IS DEPENDENT UPON ITS INSTALLATION AND USE IN COMPLETE EQUIPMENT SUBMITTED TO UL.

USE

This category covers fuseholders for Type CC, G, H, J, K, R, T and HRC fuses, special-purpose fuses, supplementary fuses, rejectors for Type C fuses, and adapters for Type S fuses, and intended for installation in end-use equipment or products.

CONDITIONS OF ACCEPTABILITY

Consideration is to be given to the Conditions of Acceptability specified in the individual Recognitions when these components are employed in the end-use equipment.

RELATED PRODUCTS


Fuseholders intended to accept supplementary fuses (miscellaneous, miniature and micro) may additionally be covered under Terminal Blocks Certified for Canada ([XCFR8](#)).

REQUIREMENTS

The basic standard used to investigate products in this category is CSA-C22.2 No. 4248.1, "Fuseholders - Part 1: General Requirements," in addition to one of the following as applicable:

- CSA-C22.2 No. 4248.4, "Fuseholders - Part 4: Class CC"
- CSA-C22.2 No. 4248.5, "Fuseholders - Part 5: Class G"
- CSA-C22.2 No. 4248.6, "Fuseholders - Part 6: Class H"
- CSA-C22.2 No. 4248.8, "Fuseholders - Part 8: Class J"
- CSA-C22.2 No. 4248.9, "Fuseholders - Part 9: Class K"
- CSA-C22.2 No. 4248.12, "Fuseholders - Part 12: Class R"
- CSA-C22.2 No. 4248.15, "Fuseholders - Part 15: Class T"

UL MARKING

Components Recognized under UL's Component Recognition Program are identified by markings consisting of the Recognized company's identification and catalog, model, or other product designation. In addition, components produced under the UL Component Recognition Program will also bear the Recognized Component Mark for Canada 

The Listing or Classification Mark of UL is not authorized for use on, or in connection with, Recognized Components. Only those components that actually bear the "Marking" should be considered as being covered under the Component Recognition Program.

UL, in performing its functions in accordance with its objectives, does not assume or undertake to discharge any responsibility of the manufacturer or any other party. UL shall not incur any obligation or liability for any loss, expense or damages, including incidental or consequential damages, arising out of or in connection with the use, interpretation of, or reliance upon this Guide Information.

[Last Updated](#) on 2010-03-05

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2021 UL LLC"

F-60-A - Fuseholders, Cartridge Fuse - Component

Fuseholders, Cartridge Fuse - Component

File Number: E101405

COMPANY**SATO PARTS CO LTD**3-3-8 Sotokanda
Chiyoda-Ku, TOKYO 101-0021 Japan**INFO**

F-60-A

RATING TABLE

Voltage Rating (V)	Ampere Rating (A)	Withstand Rating (A)	Fuse Class	Fuse Class or Size
125	5	--		5.2 mm diameter by 20 mm long

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2021 UL LLC"

F-60-B - Fuseholders, Cartridge Fuse - Component

Fuseholders, Cartridge Fuse - Component

File Number: E101405

COMPANY**SATO PARTS CO LTD**3-3-8 Sotokanda
Chiyoda-Ku, TOKYO 101-0021 Japan**INFO**

F-60-B

RATING TABLE

Voltage Rating (V)	Ampere Rating (A)	Withstand Rating (A)	Fuse Class	Fuse Class or Size
125	5	--		5.2 mm diameter by 20 mm long

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2021 UL LLC"

F-60-C - Fuseholders, Cartridge Fuse - Component

Fuseholders, Cartridge Fuse - Component

File Number: E101405

COMPANY**SATO PARTS CO LTD**3-3-8 Sotokanda
Chiyoda-Ku, TOKYO 101-0021 Japan**INFO**

F-60-C

RATING TABLE

Voltage Rating (V)	Ampere Rating (A)	Withstand Rating (A)	Fuse Class	Fuse Class or Size
125	5	--		5.2 mm diameter by 20 mm long

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2021 UL LLC"

F-61-A - Fuseholders, Cartridge Fuse - Component

Fuseholders, Cartridge Fuse - Component

File Number: E101405

COMPANY**SATO PARTS CO LTD**3-3-8 Sotokanda
Chiyoda-Ku, TOKYO 101-0021 Japan**INFO**

F-61-A

RATING TABLE

Voltage Rating (V)	Ampere Rating (A)	Withstand Rating (A)	Fuse Class	Fuse Class or Size
250	10	--		6.35 mm diameter by 31.8 mm long or 6.4 mm diameter by 30 mm long

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2021 UL LLC"

F-61-B - Fuseholders, Cartridge Fuse - Component

Fuseholders, Cartridge Fuse - Component

File Number: E101405

COMPANY**SATO PARTS CO LTD**3-3-8 Sotokanda
Chiyoda-Ku, TOKYO 101-0021 Japan**INFO**

F-61-B

RATING TABLE

Voltage Rating (V)	Ampere Rating (A)	Withstand Rating (A)	Fuse Class	Fuse Class or Size
250	10	--		6.35 mm diameter by 31.8 mm long or 6.4 mm diameter by 30 mm long

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2021 UL LLC"

F-61-C - Fuseholders, Cartridge Fuse - Component

Fuseholders, Cartridge Fuse - Component

File Number: E101405

COMPANY**SATO PARTS CO LTD**3-3-8 Sotokanda
Chiyoda-Ku, TOKYO 101-0021 Japan**INFO**

F-61-C

RATING TABLE

Voltage Rating (V)	Ampere Rating (A)	Withstand Rating (A)	Fuse Class	Fuse Class or Size
250	10	--		6.35 mm diameter by 31.8 mm long or 6.4 mm diameter by 30 mm long

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2021 UL LLC"

F-61-D - Fuseholders, Cartridge Fuse - Component

Fuseholders, Cartridge Fuse - Component

File Number: E101405

COMPANY**SATO PARTS CO LTD**3-3-8 Sotokanda
Chiyoda-Ku, TOKYO 101-0021 Japan**INFO**

F-61-D

RATING TABLE

Voltage Rating (V)	Ampere Rating (A)	Withstand Rating (A)	Fuse Class	Fuse Class or Size
250	10	--		6.35 mm diameter by 31.8 mm long or 6.4 mm diameter by 30 mm long

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2021 UL LLC"

F-64-AB - Fuseholders, Cartridge Fuse - Component

Fuseholders, Cartridge Fuse - Component

File Number: E101405

COMPANY**SATO PARTS CO LTD**3-3-8 Sotokanda
Chiyoda-Ku, TOKYO 101-0021 Japan**INFO**

F-64-AB

RATING TABLE

Voltage Rating (V)	Ampere Rating (A)	Withstand Rating (A)	Fuse Class	Fuse Class or Size
250	10	--		5.2 mm diameter by 20.0 mm long

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2021 UL LLC"

F-64-AD - Fuseholders, Cartridge Fuse - Component

Fuseholders, Cartridge Fuse - Component

File Number: E101405

COMPANY**SATO PARTS CO LTD**3-3-8 Sotokanda
Chiyoda-Ku, TOKYO 101-0021 Japan**INFO**

F-64-AD

RATING TABLE

Voltage Rating (V)	Ampere Rating (A)	Withstand Rating (A)	Fuse Class	Fuse Class or Size
250	10	--		5.2 mm diameter by 20.0 mm long

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2021 UL LLC"

F-64-BB - Fuseholders, Cartridge Fuse - Component

Fuseholders, Cartridge Fuse - Component

File Number: E101405

COMPANY**SATO PARTS CO LTD**3-3-8 Sotokanda
Chiyoda-Ku, TOKYO 101-0021 Japan**INFO**

F-64-BB

RATING TABLE

Voltage Rating (V)	Ampere Rating (A)	Withstand Rating (A)	Fuse Class	Fuse Class or Size
250	10	--		5.2 mm diameter by 20.0 mm long

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2021 UL LLC"

F-64-BD - Fuseholders, Cartridge Fuse - Component

Fuseholders, Cartridge Fuse - Component

File Number: E101405

COMPANY**SATO PARTS CO LTD**3-3-8 Sotokanda
Chiyoda-Ku, TOKYO 101-0021 Japan**INFO**

F-64-BD

RATING TABLE

Voltage Rating (V)	Ampere Rating (A)	Withstand Rating (A)	Fuse Class	Fuse Class or Size
250	10	--		5.2 mm diameter by 20.0 mm long

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2021 UL LLC"

F-65-AB - Fuseholders, Cartridge Fuse - Component

Fuseholders, Cartridge Fuse - Component

File Number: E101405

COMPANY**SATO PARTS CO LTD**3-3-8 Sotokanda
Chiyoda-Ku, TOKYO 101-0021 Japan**INFO**

F-65-AB

RATING TABLE

Voltage Rating (V)	Ampere Rating (A)	Withstand Rating (A)	Fuse Class	Fuse Class or Size
250	10	--		31.8 mm by 6.35 mm diameter or 30 mm by 6.4 mm diameter

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2021 UL LLC"

F-65-AD - Fuseholders, Cartridge Fuse - Component

Fuseholders, Cartridge Fuse - Component

File Number: E101405

COMPANY

SATO PARTS CO LTD

3-3-8 Sotokanda

Chiyoda-Ku, TOKYO 101-0021 Japan

INFO

F-65-AD

RATING TABLE

Voltage Rating (V)	Ampere Rating (A)	Withstand Rating (A)	Fuse Class	Fuse Class or Size
250	10	--		31.8 mm by 6.35 mm diameter or 30 mm by 6.4 mm diameter

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2021 UL LLC"

F-65-BB - Fuseholders, Cartridge Fuse - Component

Fuseholders, Cartridge Fuse - Component

File Number: E101405

COMPANY**SATO PARTS CO LTD**3-3-8 Sotokanda
Chiyoda-Ku, TOKYO 101-0021 Japan**INFO**

F-65-BB

RATING TABLE

Voltage Rating (V)	Ampere Rating (A)	Withstand Rating (A)	Fuse Class	Fuse Class or Size
250	10	--		31.8 mm by 6.35 mm diameter or 30 mm by 6.4 mm diameter

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2021 UL LLC"

F-65-BD - Fuseholders, Cartridge Fuse - Component

Fuseholders, Cartridge Fuse - Component

File Number: E101405

COMPANY**SATO PARTS CO LTD**3-3-8 Sotokanda
Chiyoda-Ku, TOKYO 101-0021 Japan**INFO**

F-65-BD

RATING TABLE

Voltage Rating (V)	Ampere Rating (A)	Withstand Rating (A)	Fuse Class	Fuse Class or Size
250	10	--		31.8 mm by 6.35 mm diameter or 30 mm by 6.4 mm diameter

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2021 UL LLC"

F-66-AD - Fuseholders, Cartridge Fuse - Component

Fuseholders, Cartridge Fuse - Component

File Number: E101405

COMPANY**SATO PARTS CO LTD**3-3-8 Sotokanda
Chiyoda-Ku, TOKYO 101-0021 Japan**INFO**

F-66-AD

RATING TABLE

Voltage Rating (V)	Ampere Rating (A)	Withstand Rating (A)	Fuse Class	Fuse Class or Size
250	10	--		38.1 mm by 10.31 mm diameter

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2021 UL LLC"

F-66-AF - Fuseholders, Cartridge Fuse - Component

Fuseholders, Cartridge Fuse - Component

File Number: E101405

COMPANY**SATO PARTS CO LTD**3-3-8 Sotokanda
Chiyoda-Ku, TOKYO 101-0021 Japan**INFO**

F-66-AF

RATING TABLE

Voltage Rating (V)	Ampere Rating (A)	Withstand Rating (A)	Fuse Class	Fuse Class or Size
250	20	--		38.1 mm by 10.31 mm diameter

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2021 UL LLC"

F-66-BD - Fuseholders, Cartridge Fuse - Component

Fuseholders, Cartridge Fuse - Component

File Number: E101405

COMPANY

SATO PARTS CO LTD

3-3-8 Sotokanda
Chiyoda-Ku, TOKYO 101-0021 Japan

INFO

F-66-BD

RATING TABLE

Voltage Rating (V)	Ampere Rating (A)	Withstand Rating (A)	Fuse Class	Fuse Class or Size
250	20	--		38.1 mm by 10.31 mm diameter

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2021 UL LLC"

F-66-BF - Fuseholders, Cartridge Fuse - Component

Fuseholders, Cartridge Fuse - Component

File Number: E101405

COMPANY**SATO PARTS CO LTD**3-3-8 Sotokanda
Chiyoda-Ku, TOKYO 101-0021 Japan**INFO**

F-66-BF

RATING TABLE

Voltage Rating (V)	Ampere Rating (A)	Withstand Rating (A)	Fuse Class	Fuse Class or Size
250	20	--		38.1 mm by 10.31 mm diameter

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2021 UL LLC"

F-70 - Fuseholders, Cartridge Fuse - Component

Fuseholders, Cartridge Fuse - Component

File Number: E101405

COMPANY**SATO PARTS CO LTD**3-3-8 Sotokanda
Chiyoda-Ku, TOKYO 101-0021 Japan**INFO**

F-70

RATING TABLE

Voltage Rating (V)	Ampere Rating (A)	Withstand Rating (A)	Fuse Class	Fuse Class or Size
250	30	--		31.8 mm by 6.35 mm diameter

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2021 UL LLC"

F-75 - Fuseholders, Cartridge Fuse - Component

Fuseholders, Cartridge Fuse - Component

File Number: E101405

COMPANY**SATO PARTS CO LTD**3-3-8 Sotokanda
Chiyoda-Ku, TOKYO 101-0021 Japan**INFO**

F-75

RATING TABLE

Voltage Rating (V)	Ampere Rating (A)	Withstand Rating (A)	Fuse Class	Fuse Class or Size
250	10	--		20 mm by 5.2 mm diameter

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2021 UL LLC"

F-85 - Fuseholders, Cartridge Fuse - Component

Fuseholders, Cartridge Fuse - Component

File Number: E101405

COMPANY**SATO PARTS CO LTD**3-3-8 Sotokanda
Chiyoda-Ku, TOKYO 101-0021 Japan**INFO**

F-85

RATING TABLE

Voltage Rating (V)	Ampere Rating (A)	Withstand Rating (A)	Fuse Class	Fuse Class or Size
250	10	--		31.8 mm by 6.35 mm diameter

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2021 UL LLC"

F-100 - Fuseholders, Cartridge Fuse - Component

Fuseholders, Cartridge Fuse - Component

File Number: E101405

COMPANY

SATO PARTS CO LTD

3-3-8 Sotokanda

Chiyoda-Ku, TOKYO 101-0021 Japan

INFO

F-100

RATING TABLE

Voltage Rating (V)	Ampere Rating (A)	Withstand Rating (A)	Fuse Class	Fuse Class or Size
250	10	--		20 mm by 5.2 mm diameter

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2021 UL LLC"

F 105 - Fuseholders, Cartridge Fuse - Component

Fuseholders, Cartridge Fuse - Component

File Number: E101405

COMPANY**SATO PARTS CO LTD**3-3-8 Sotokanda
Chiyoda-Ku, TOKYO 101-0021 Japan**INFO**

F 105

RATING TABLE

Voltage Rating (V)	Ampere Rating (A)	Withstand Rating (A)	Fuse Class	Fuse Class or Size
250	10	--		5.2 mm diameter by 20 mm long

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2021 UL LLC"

F-100 - Fuseholders, Cartridge Fuse - Component

Fuseholders, Cartridge Fuse - Component

File Number: E101405

COMPANY**SATO PARTS CO LTD**3-3-8 Sotokanda
Chiyoda-Ku, TOKYO 101-0021 Japan**INFO**

F-100

RATING TABLE

Voltage Rating (V)	Ampere Rating (A)	Withstand Rating (A)	Fuse Class	Fuse Class or Size
250	10	--		20 mm by 5.2 mm diameter

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2021 UL LLC"

F-110 - Fuseholders, Cartridge Fuse - Component

Fuseholders, Cartridge Fuse - Component

File Number: E101405

COMPANY**SATO PARTS CO LTD**3-3-8 Sotokanda
Chiyoda-Ku, TOKYO 101-0021 Japan**INFO**

F-110

RATING TABLE

Voltage Rating (V)	Ampere Rating (A)	Withstand Rating (A)	Fuse Class	Fuse Class or Size
250	10	--		31.8 mm by 6.35 mm diameter or 30 mm by 6.4 mm diameter

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2021 UL LLC"

F-115

File Number: E101405

COMPANY**SATO PARTS CO LTD**

3-3-8 Sotokanda

Chiyoda-Ku, TOKYO 101-0021 Japan

INFO

F-115

RATING TABLE

Voltage Rating (V)	Ampere Rating (A)	Withstand Rating (A)	Fuse Class	Fuse Class or Size
250	6	--		5.2 mm diameter by 20 mm long

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2021 UL LLC"

F-120-A - Fuseholders, Cartridge Fuse - Component

Fuseholders, Cartridge Fuse - Component

File Number: E101405

COMPANY**SATO PARTS CO LTD**3-3-8 Sotokanda
Chiyoda-Ku, TOKYO 101-0021 Japan**INFO**

F-120-A

RATING TABLE

Voltage Rating (V)	Ampere Rating (A)	Withstand Rating (A)	Fuse Class	Fuse Class or Size
250	10	--		6.4 mm diameter by 31.8 mm long

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2021 UL LLC"

F-120-B - Fuseholders, Cartridge Fuse - Component

Fuseholders, Cartridge Fuse - Component

File Number: E101405

COMPANY**SATO PARTS CO LTD**3-3-8 Sotokanda
Chiyoda-Ku, TOKYO 101-0021 Japan**INFO**

F-120-B

RATING TABLE

Voltage Rating (V)	Ampere Rating (A)	Withstand Rating (A)	Fuse Class	Fuse Class or Size
250	10	--		6.4 mm diameter by 31.8 mm long

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2021 UL LLC"

F-130 - Fuseholders, Cartridge Fuse - Component

Fuseholders, Cartridge Fuse - Component

File Number: E101405

COMPANY

SATO PARTS CO LTD

3-3-8 Sotokanda

Chiyoda-Ku, TOKYO 101-0021 Japan

INFO

F-130

RATING TABLE

Voltage Rating (V)	Ampere Rating (A)	Withstand Rating (A)	Fuse Class	Fuse Class or Size
250	10	--		6.4 mm diameter by 31.8 mm long

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2021 UL LLC"

F-200-N

File Number: E101405

COMPANY**SATO PARTS CO LTD**3-3-8 Sotokanda
Chiyoda-Ku, TOKYO 101-0021 Japan**INFO**

F-200-N

RATING TABLE

Voltage Rating (V)	Ampere Rating (A)	Withstand Rating (A)	Fuse Class	Fuse Class or Size
250	10	--		6.35 mm diameter by 31.8 mm long or 6.4 mm diameter by 30 mm long

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2021 UL LLC"

F-240-N

File Number: E101405

COMPANY**SATO PARTS CO LTD**3-3-8 Sotokanda
Chiyoda-Ku, TOKYO 101-0021 Japan**INFO****F-240-N****RATING TABLE**

Voltage Rating (V)	Ampere Rating (A)	Withstand Rating (A)	Fuse Class	Fuse Class or Size
250	10	--		6.35 mm diameter by 31.8 mm long or 6.4 mm diameter by 30 mm long

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2021 UL LLC"

F-300-1P - Fuseholders, Cartridge Fuse - Component

Fuseholders, Cartridge Fuse - Component

File Number: E101405

COMPANY**SATO PARTS CO LTD**3-3-8 Sotokanda
Chiyoda-Ku, TOKYO 101-0021 Japan**INFO**

F-300-1P

RATING TABLE

Voltage Rating (V)	Ampere Rating (A)	Withstand Rating (A)	Fuse Class	Fuse Class or Size
250	5	--		5 mm diameter by 20 mm long

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2021 UL LLC"

F-300-2P - Fuseholders, Cartridge Fuse - Component

Fuseholders, Cartridge Fuse - Component

File Number: E101405

COMPANY**SATO PARTS CO LTD**3-3-8 Sotokanda
Chiyoda-Ku, TOKYO 101-0021 Japan**INFO**

F-300-2P

RATING TABLE

Voltage Rating (V)	Ampere Rating (A)	Withstand Rating (A)	Fuse Class	Fuse Class or Size
250	5	--		5 mm diameter by 20 mm long

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2021 UL LLC"

F-300-3P - Fuseholders, Cartridge Fuse - Component

Fuseholders, Cartridge Fuse - Component

File Number: E101405

COMPANY**SATO PARTS CO LTD**3-3-8 Sotokanda
Chiyoda-Ku, TOKYO 101-0021 Japan**INFO**

F-300-3P

RATING TABLE

Voltage Rating (V)	Ampere Rating (A)	Withstand Rating (A)	Fuse Class	Fuse Class or Size
250	5	--		5 mm diameter by 20 mm long

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2021 UL LLC"

F-400-01A1

File Number: E101405

COMPANY**SATO PARTS CO LTD**3-3-8 Sotokanda
Chiyoda-Ku, TOKYO 101-0021 Japan**INFO**

F-400-01A1

RATING TABLE

Voltage Rating (V)	Ampere Rating (A)	Withstand Rating (A)	Fuse Class	Fuse Class or Size
250	10	--		6.35 mm diameter by 31.8 mm long or 6.4 mm diameter by 30 mm long

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2021 UL LLC"

F-400-01A2

File Number: E101405

COMPANY**SATO PARTS CO LTD**3-3-8 Sotokanda
Chiyoda-Ku, TOKYO 101-0021 Japan**INFO**

F-400-01A2

RATING TABLE

Voltage Rating (V)	Ampere Rating (A)	Withstand Rating (A)	Fuse Class	Fuse Class or Size
250	10	--		5.2 mm diameter by 20.0 mm long

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2021 UL LLC"

F-400-01B1

File Number: E101405

COMPANY**SATO PARTS CO LTD**3-3-8 Sotokanda
Chiyoda-Ku, TOKYO 101-0021 Japan**INFO**

F-400-01B1

RATING TABLE

Voltage Rating (V)	Ampere Rating (A)	Withstand Rating (A)	Fuse Class	Fuse Class or Size
250	10	--		6.35 mm diameter by 31.8 mm long or 6.4 mm diameter by 30 mm long

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2021 UL LLC"

F-400-01B2

File Number: E101405

COMPANY**SATO PARTS CO LTD**3-3-8 Sotokanda
Chiyoda-Ku, TOKYO 101-0021 Japan**INFO**

F-400-01B2

RATING TABLE

Voltage Rating (V)	Ampere Rating (A)	Withstand Rating (A)	Fuse Class	Fuse Class or Size
250	10	--		5.2 mm diameter by 20.0 mm long

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2021 UL LLC"

F-450

File Number: E101405

COMPANY**SATO PARTS CO LTD**3-3-8 Sotokanda
Chiyoda-Ku, TOKYO 101-0021 Japan**INFO**

F-450

RATING TABLE

Voltage Rating (V)	Ampere Rating (A)	Withstand Rating (A)	Fuse Class	Fuse Class or Size
300	25	--		6.4mm diameter by 30 mm long or 6.35mm diameter by 30 mm long

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2021 UL LLC"

F-500-01A1

File Number: E101405

COMPANY**SATO PARTS CO LTD**

3-3-8 Sotokanda

Chiyoda-Ku, TOKYO 101-0021 Japan

INFO

F-500-01A1

RATING TABLE

Voltage Rating (V)	Ampere Rating (A)	Withstand Rating (A)	Fuse Class	Fuse Class or Size
250	10	--		6.35 mm diameter by 31.8 mm long or 6.4 mm diameter by 30 mm long

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2021 UL LLC"

F-500-01A2

File Number: E101405

COMPANY**SATO PARTS CO LTD**3-3-8 Sotokanda
Chiyoda-Ku, TOKYO 101-0021 Japan**INFO**

F-500-01A2

RATING TABLE

Voltage Rating (V)	Ampere Rating (A)	Withstand Rating (A)	Fuse Class	Fuse Class or Size
250	10	--		5.2 mm diameter by 20.0 mm long

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2021 UL LLC"

F-500-01B1

File Number: E101405

COMPANY**SATO PARTS CO LTD**3-3-8 Sotokanda
Chiyoda-Ku, TOKYO 101-0021 Japan**INFO**

F-500-01B1

RATING TABLE

Voltage Rating (V)	Ampere Rating (A)	Withstand Rating (A)	Fuse Class	Fuse Class or Size
250	10	--		6.35 mm diameter by 31.8 mm long or 6.4 mm diameter by 30 mm long

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2021 UL LLC"

F-500-01B2

File Number: E101405

COMPANY**SATO PARTS CO LTD**3-3-8 Sotokanda
Chiyoda-Ku, TOKYO 101-0021 Japan**INFO**

F-500-01B2

RATING TABLE

Voltage Rating (V)	Ampere Rating (A)	Withstand Rating (A)	Fuse Class	Fuse Class or Size
250	10	--		5.2 mm diameter by 20.0 mm long

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2021 UL LLC"

F-600

File Number: E101405

COMPANY**SATO PARTS CO LTD**3-3-8 Sotokanda
Chiyoda-Ku, TOKYO 101-0021 Japan**INFO**

F-600

RATING TABLE

Voltage Rating (V)	Ampere Rating (A)	Withstand Rating (A)	Fuse Class	Fuse Class or Size
250	8	--		5.2 mm diameter by 20 mm long

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2021 UL LLC"

F-610

File Number: E101405

COMPANY**SATO PARTS CO LTD**3-3-8 Sotokanda
Chiyoda-Ku, TOKYO 101-0021 Japan**INFO**

F-610

RATING TABLE

Voltage Rating (V)	Ampere Rating (A)	Withstand Rating (A)	Fuse Class	Fuse Class or Size
250	8	--		6.35 mm diameter by 31.8 mm long or 6.4 mm diameter by 30 mm long

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2021 UL LLC"

F-700

File Number: E101405

COMPANY**SATO PARTS CO LTD**

3-3-8 Sotokanda

Chiyoda-Ku, TOKYO 101-0021 Japan

INFO

F-700 may be followed by -A or -B, may be followed by L, may be followed by -2P to 30P

RATING TABLE

Voltage Rating (V)	Ampere Rating (A)	Withstand Rating (A)	Fuse Class	Fuse Class or Size
250	10	--		6.4mm diameter by 30 mm long, 6.35mm diameter by 30 mm long or 6.35 mm diameter by 31.8mm long

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2021 UL LLC"

F-710

File Number: E101405

COMPANY**SATO PARTS CO LTD**

3-3-8 Sotokanda

Chiyoda-Ku, TOKYO 101-0021 Japan

INFO

F-710 may be followed by -A or -B, may be followed by -2P to -30P

RATING TABLE

Voltage Rating (V)	Ampere Rating (A)	Withstand Rating (A)	Fuse Class	Fuse Class or Size
250	10	--		5.2 mm diameter by 20 mm

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2021 UL LLC"

F-720

File Number: E101405

COMPANY**SATO PARTS CO LTD**3-3-8 Sotokanda
Chiyoda-Ku, TOKYO 101-0021 Japan**INFO**

F-720 may be followed by -L, may be followed by -2P to -30P

RATING TABLE

Voltage Rating (V)	Ampere Rating (A)	Withstand Rating (A)	Fuse Class	Fuse Class or Size
250	20	--		10.3 mm diameter by 38.0 mm long

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2021 UL LLC"

F-750

File Number: E101405

COMPANY**SATO PARTS CO LTD**

3-3-8 Sotokanda

Chiyoda-Ku, TOKYO 101-0021 Japan

INFO

F-750 may be followed by -2P to -30P

RATING TABLE

Voltage Rating (V)	Ampere Rating (A)	Withstand Rating (A)	Fuse Class	Fuse Class or Size
250	15	--		6.4mm diameter by 30mm long, 6.35mm diameter by 30mm long or 6.35mm diameter by 31.8mm long

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2021 UL LLC"

F-4000-A

File Number: E101405

COMPANY**SATO PARTS CO LTD**

3-3-8 Sotokanda

Chiyoda-Ku, TOKYO 101-0021 Japan

INFO

F-4000-A

RATING TABLE

Voltage Rating (V)	Ampere Rating (A)	Withstand Rating (A)	Fuse Class	Fuse Class or Size
250	10	--		6.4 mm diameter by 30 mm long

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2021 UL LLC"

F-4000-B

File Number: E101405

COMPANY**SATO PARTS CO LTD**3-3-8 Sotokanda
Chiyoda-Ku, TOKYO 101-0021 Japan**INFO**

F-4000-B

RATING TABLE

Voltage Rating (V)	Ampere Rating (A)	Withstand Rating (A)	Fuse Class	Fuse Class or Size
250	10	--		6.4 mm diameter by 30 mm long

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2021 UL LLC"